

# TAKE A DOUBLE LOOK!



WP10-BW

WP20-BW

# BIG WHITE™ FILTER HOUSINGS

Our large capacity Big White™ Series Housings are manufactured with only FDA compliant, reinforced Polypropylenes. With our unique "Square Cut Gasket" seal, testing has been satisfactorily completed in accordance to WQA's Voluntary Standards S-300 Appendix D, under sections 3.1, 3.2, and 3.3.

Our Big White™ Series Housings are available with 1/2", 3/4", 1", and 1-1/2" NPT caps. We also offer a 1" BSP (metric) inlet/outlet. All caps are standard stock items with a pressure relief button, however, caps without a pressure relief button are available as a specialty item upon request.



## EXTERNAL DIMENSIONS

WP10-BW (1"):	7-1/4" x 13-1/2"	WP10-BW (1-1/2"):	7 1/4" x 13-7/8"
WP20-BW (1"):	7-1/4" x 23-3/4"	WP20-BW (1-1/2"):	7 1/4" x 24-1/8"

## INTERNAL DIMENSIONS

WP10-BW: Will accommodate 9-3/4" and 9-7/8" x 4-1/2" cartridges

WP20-BW: Will accommodate 20" x 4-1/2" cartridges

(will accommodate Fibredyne, Ametek and KX Industries carbon filters)

## MAXIMUM OPERATING PRESSURE

Both WP10-BW and WP20-BW: 125 psi

## MAXIMUM TEMPERATURE

Both WP10-BW and WP20-BW: 125° F

## PACKAGING

Both WP10-BW and WP20-BW housings are individually boxed, then master cartoned four units per master.

WP10-BW:	individual box dims:	7-3/8" x 7-3/8" x 14"	(weight: 5-1/2 lbs)
WP10-BW:	master box dims:	15-5/8" x 15-5/8" x 15"	(weight: 22 lbs)
WP20-BW:	individual box dims:	7-3/8" x 7-3/8" x 24-1/4"	(weight: 8 lbs)
WP20-BW:	master box dims:	15-5/8" x 15-5/8" x 24-1/2"	(weight: 32 lbs)

## AVAILABLE ACCESSORIES FOR BIG WHITE™ HOUSINGS

- BW-FHWR: Full Housing wrench, to make filter replacing a breeze and eliminate damage to the housing and your hands.
- BWI: White, powder coated, bracket kit with four mounting screws.

## AVAILABLE FILTER CARTRIDGES

- Polymicro®: "Melt Blown" sediment filters, featuring Graded "Pore" Construction achieved through proprietary melt blown process. This unique process develops a cartridge with enormous quantities of progressively smaller pores without significantly increasing bulk density. Available in: 5, 10, 25, and 50 micron (nominal) ratings.
- Pleated Filters: All synthetic, cleanable and re-usable sediment filters. This product is fantastic for specific applications, such as for pools and spas. Being that this product is used in pools and spas, imagine how wonderful it will perform in your drinking water application. Available in: 5, 10, 20, and 50 micron (nominal) ratings.



Caution: If you suspect that your water pressure will at any time exceed the maximum rating of 125 psi, a pressure regulator must be installed before the filter. It is recommended that the pressure regulator be set at 75 psi or less. All products must be kept from freezing.