

ink erator®

Information contact

Highway  
3153

136 205  
20 3178  
insinkerator.com.au

ator.com.au



in sink erator®

Discover the new style  
of convenience.

InSinkErator® Steaming Hot Water Tap



is a registered

tric Co.  
trademark of  
tric Co.  
2006

  
**EMERSON**  
Appliance Solutions

  
**EMERSON**  
Appliance Solutions



erator® all new  
steaming hot water  
taps are near-  
boiling right at  
the sink.  
Controlled by a lever,  
they offer the style  
and convenience.

The stainless steel tank  
heats water to  
near 98°C.  
Filtered water is  
drawn from the  
tap and enters  
the heating element  
for quick heating.  
The HC1100 model also  
dispenses ambient  
filtered water.  
A fast  
dispenser can  
dispense 100 cups  
of water per  
hour. The single-lever  
dispenser is  
easier than a  
two-lever.

The HC1100 is in the range,  
the GN1100 is ambient,  
the H990 is a dispenser  
model to  
fit the kitchen.

The steaming hot  
water is available  
in a variety of  
finishes and  
models.



Find your best retailer,  
call 1300 205 or visit  
erator.com.au

### HC1100 Steaming hot and ambient filtered water

- Two lever dispenser
- 100 near boiling cups per hour
- Reduce bench-top clutter
- 5 Micron filter
- 2 year warranty

#### HC1100 specifications

Capacity	2.5 Litre Stainless Steel tank dispenses 100 cups of 98°C water per hour
Electrical	220 – 240 volts A.C. 1300 watts, heating element with grounded three (3) pin plug
Thermostat	Electronic, adjustable from 88°C to 98°C (factory pre-set at 96°C)
Hot Valve	Instant, self closing
Weight	Approximately 5.5kg empty
Required Hole Diameter	35mm – 38mm
Required Supply Pressure	172 – 862 KPa (1.7 – 8.6 bar) (25 – 125 psi)





### GN1100 Steaming hot filtered water

- Single lever dispenser
- 100 near boiling cups per hour
- Reduce bench-top clutter
- 5 Micron filter
- 2 year warranty

#### GN1100 specifications

Capacity	2.5 Litre Stainless Steel tank dispenses 100 cups of 98°C water per hour
Electrical	220 – 240 volts A.C. 1300 watts, heating element with grounded three (3) pin plug
Thermostat	Electronic, adjustable from 88°C to 98°C (factory pre-set at 96°C)
Hot Valve	Instant, self closing
Weight	Approximately 5.5kg empty
Required Hole Diameter	35mm – 38mm
Required Supply Pressure	172 – 862 KPa (1.7 – 8.6 bar) (25 – 125 psi)



### H990 Steaming hot water

- Swivel handle dispenser
- 100 near boiling cups per hour
- Reduce bench-top clutter
- No more noisy kettles
- 2 year warranty

#### H990 specifications

Capacity	2.5 Litre Stainless Steel tank dispenses 100 cups of 98°C water per hour
Electrical	220 – 240 volts A.C. 1300 watts, heating element with grounded three (3) pin plug
Thermostat	Electronic, adjustable from 88°C to 98°C (factory pre-set at 96°C)
Hot Valve	Instant, self closing
Weight	Approximately 4.0kg empty
Required Hole Diameter	32mm – 38mm
Required Supply Pressure	172 – 862 KPa (1.7 – 8.6 bar) (25 – 125 psi)

