

Ceramic Single Countertop

featuring the Doulton Ultracarb®

0.9 Micron Absolute Rating Advanced micro-biological protection Space Saving, Portable Design Ideal for renters

5 Year Warranty*
Hand built in Australia





The Ceramic Single Countertop provides a supreme quality, cost effective and portable method of water filtration. This unique system stands conveniently on your countertop for easy 'self' installation to your existing faucet, using the special diverter valve provided.

◆ Fitted with the Doulton Ultracarb® filter cartridge this system provides micro-biologically safe, great tasting drinking water on demand.

Filtration Test Results

Impurities	% Reduction
Cysts	100
Bacteria	99.99
Residual Chlorine Content	99.0
Trihalomethanes:	
Bromodichloromethane	99.3
Bromoform	99.3
Chloroform	99.5
Dibromochloromethane	99.3
Heavy Metals:	
Zinc	99.7
Lead, Manganese, Cadium	99.9
Copper, Mercury	99.9
Aluminium	98.7

WaterMark Certificate No.: 23124

The Australian WaterMark Standard Approval of this system is your guarantee of quality.

Specifications

Item Code	IT000421
Filter Output	5,000 litres
Max Flow Rate	3 litres p/min
Dimensions (cm)	15(W) x 30(H)
Micron Rating	0.9 micron absolute
Warranty	5 years*

Filtration Process Diagram 1

Sediment/Dirt, Rust, e-Coli, Cholera, Shigella, Typhoid, Cryptosporidium, Giardia CERAMIC

Chemicals & Heavy Metals CARBON

Premium Water
(to faucet)

Ceramic Single Countertop

SINGLE STAGE

The Doulton UltraCarb® Filter Cartridge

0.9 micron absolute Made in UK




 Ceramic Outer Shell: Mechanically filters out harmful bacteria and parasites.

Manufactured with Doulton Sterasyl® ceramic which provides genuine sub-micron filtration. This stage reduces fine particulate matter, bacteria, cysts and turbidity. Silver, incorporated within this ceramic structure provides enhanced bacteriostatic and self sterilising, anti-bacterial properties.

◆ Carbon Block Inner Core: Reduces chlorine and organic compounds.

The Doulton Ultracarb® cartridge features premium carbon made from the highest quality NSF certified (ANSI 61) coconut shell based granular activated carbon and other proprietary adsorbent medias.



lon exchange resin incorporated within the inner core effectively reduces lead, zinc and other heavy metals.



The Doulton Ultracarb® fiter cartridge can be washed and reused

If the flow rate slows, simply scrub clean under cold, running water with a clean sponge or brush*.

System Assembly Diagram 2





To consult our **Countertop Maintenance Guide** please visit: www.watershop.com.au.

This system connects to your existing faucet using the diverter included. Simply remove/unscrew the existing aerator off your existing faucet and connect/screw on the diverter valve.

Labelled Components

A	Doulton Ultracarb® Filter	4	Housing Stand
1	Housing Sump	5	Inlet
2	Stainless Steel Spout	6	Hose
3	Outlet	7	Diverter



North Shore Showroom 425 Miller Street. Cammeray NSW 2062 Inner West Showroom 342-350 Parramatta Road, Stanmore NSW 2048

02 9458 1111 sales@watershop.com.au www.watershop.com.au